


Pure Sine Wave



[6sq*2.7M]

Outer size and specifications



▪ Specifications for each model (24V-220V)

No.	PARAMETER		KEY260S		KEY280S	KEY1002S	LIMIT
1	DC input voltage		24V				20V-30V
2	DC input voltage standard		26.8V				
3	Output voltage no load		AC225V				AC220V ±5%
4	Output power max		600W	800W	1000W		±5%
5	Surge rating		1200W	1500W	2000W		±5%
6	Output power continuous		480W	650W	800W		±5%
7	Efficiency (output)		89%				±3%
8	THD[max]		360W 1.1%	360W 1.1%	360W 1.1%		MAX 2.5%
9	No load current	no fan	0.35A	0.47A	0.34A		±0.1A
		on fan	0.50A	0.62A	0.49A		
10	Low battery shut down		DC 20.0V				±0.5V
11	Low battery return on power		22.0V				±0.5V
12	High battery shut down		DC 30.0V				±1.0V
13	High battery return on power		28.0V				±0.5V
14	Frequency selection[50hz/60hz]		60Hz [50Hz,60Hz & 50Hz Specifications of order]	60Hz & 50Hz			±0.3hz
15	Regulation		max5% within				-
16	Temperature characteristics		-25℃ ~ 72℃ (temperature inside)				75℃ ±5℃
17	Over temperature power on		58℃ (temperature inside)				±5℃
18	Output wave form		Pure sine wave (D.S.P)				-
19	Cooling fan(auto fan)		fan on temperature 45℃ on				-
20	Overload protection	input circuit breaker	-				maximum output +300W
		output circuit breaker	-				
		input/output fuse	800W	1000W	1300W		
		overheat temperature	72℃				±5℃
21	Dimensions		186×74×240	186×74×270	186×74×290		
22	Weight / color		1.5kg/Silver	1.7kg/Silver	2.9kg/Silver		

▪ Devices used

Induction, electric/electronic products with built-in inverter circuit

[Air conditioner (for about 20m² - 3kw or above), electric rice cookers (electronic type), electric pad (electronic type), fans (electronic type), refrigerators, imported refrigerators, chargers (electrically powered, for communication devices, recharging pack), three-phase inverters, motor controllers, PLC circuits, devices with built-in control function]

LED lamps exceeding 100W, laser printers, precision test devices, precision medical equipment, communication/video/audio devices, solar lights, mercury lamps/halogens/HQI, non-linear load, motor pumps, coil load/trans, other electric/electronic products, devices malfunctioning under modified sine wave

✖ **The power consumption of various devices used (electric/electronic products) shall be within the output range of the inverter.**

✖ To improve performance, product specification can be changed without notice.



فروشگاه اروین سولار

تلفن: ۰۲۱ - ۳۳۹۹۹۰۵۶
هت بلند ۰۲۱ - ۳۳۹۹۹۰۷۲

www.ervinsolar.ir
ervinsolar@hotmail.com