

Product Characteristics

Model No.	ODA320-36-P	ODA325-36-P	ODA330-36-P	ODA335-36-P	ODA340-36-P	ODA345-36-P	>
Warranty							
Product Warranty	12 Years						
Power Warranty	10 Years of 90% Output Power, 25 Years of 80% Output Power						
Electrical Data at STC							
Maximum Power (Pmax)	320 Wp	325 Wp	330 Wp	335 Wp	340 Wp	345 Wp	
Voltage at Maximum Power (Vmpp)	36.78 V	37.14 V	37.26 V	37.31 V	37.42 V	37.56 V	
Current at Maximum Power (Impp)	8.71 A	8.76 A	8.86 A	8.98 A	9.09 A	9.19 A	
Open Circuit Voltage (Voc)	44.14 V	44.57 V	44.72 V	44.78 V	44.9 V	45.07 V	
Short Circuit Current (Isc)	9.41 A	9.46 A	9.57 A	9.7 A	9.82 A	9.93 A	
Panel Efficiency	16.49 %	16.74 %	17 %	17.26 %	17.52 %	17.78 %	

Temperature Coefficient of Voc	-0.3 %/°C
Temperature Coefficient of Isc	0.06 %/°C
Maximum Ratings	
Maximum System Voltage	1500 V
Series Fuse Rating	20 A
Material Data	
Panel Dimension (H/W/D) ?	1956x992x40 mm
Weight	22.5 kg
Cell Type	Polycrystalline
Cell Size	156.75×156.75 mm
Cell Number	72
Glass Type	Tempered, High Transmittance, Low Iron
Glass Thickness	3.2 mm
Frame Type	Anodized Aluminium Alloy

Temperature Coefficient of Voc	-0.3 %/°C
Temperature Coefficient of Isc	0.06 %/°C
Maximum Ratings	
Maximum System Voltage	1500 V
Series Fuse Rating	20 A
Material Data	
Panel Dimension (H/W/D) ?	1956x992x40 mm
Weight	22.5 kg
Cell Type	Polycrystalline
Cell Size	156.75×156.75 mm
Cell Number	72
Glass Type	Tempered, High Transmittance, Low Iron
Glass Thickness	3.2 mm
Frame Type	Anodized Aluminium Alloy

[illegible]