



Inspiring green-energy since 2003

PERC Technology

AE BIFACIAL SINGLE GLASS MONOCRYSTALLINE PV MODULES AE M6-72 Series 370W-385W

72

CELLS



MICRO-CRACK
FREE



PID
RESISTANT



SALT CORROSION
RESISTANT



SAND
RESISTANT



AMMONIA
RESISTANT



HIGHLY STABLE
AND TOUGH



✓ GERMAN QUALITY
AE Solar photovoltaic modules are produced using high quality materials, automated robotic lines, German technology and standards.

+ PLUS-SORTING
Higher yield due to plus-sorting from 0 up to +5 Wp guarantees the high system efficiency and yield stability.

⌚ PERFORMANCE GUARANTEE
AE Solar assures high investment, security and warranty claims by providing linear performance guarantee of 30 years and 12 years of product warranty.

📄 CERTIFICATES
Lining with international standards, AE Solar Photovoltaic modules are tested and certified under extreme stress conditions and it can bear harsh environment influences.

OUR PERFORMANCE GUARANTEE



Deutsche
Qualität
Garantiert

TECHNICAL DATA

AE M6-72 Series 370W-385W

SPECIFICATIONS

AE370M6-72

AE375GM6-72

AE380M6-72

AE385M6-72

Nominal Max. Power	P _{max} (Wp)	370	375	380	385
Maximum power voltage	V _{mp} (V)	41.96	42.33	42.74	43.11
Maximum power current	I _{mp} (A)	8.82	8.86	8.89	8.93
Open-circuit voltage	V _{oc} (V)	45.12	50.23	50.74	51.14
Short-circuit current	I _{sc} (A)	9.41	9.45	9.48	9.53
Module efficiency	(%)	19.07	19.33	19.58	19.84
Power tolerance	P _{max} (Wp)	0 / +4.99			
Maximum system voltage DC	(V)	1500			
Maximum series fuse rating	(A)	20			
Operating temperature	(°C)	-40 to +85			
Temp. coefficients of P _{max}	(%/°C)	-0.436			
Temp. coefficients of V _{oc}	(%/°C)	-0.325			
Temp. coefficients of I _{sc}	(%/°C)	0.054			
Nom. Operating cell temp.(NOCT)	(°C)	45±2			

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.

MATERIAL CHARACTERISTICS

Cell type	Mono-crystalline 156.75mm x 156.75mm
No. of cells	72 (6 x 12)
Dimensions	1956 x 992 x 40mm
Weight	21 kg
Junction box	IP 67 rated
Output cable	1 x 4.0mm ² , 1200mm length or customised
Connector type	MC 4 / MC 4 compatible
Hail resistance	Max. Ø 28 mm, at 23 m/s
Wind load	2400 Pa / 244 kg/m ²
Mechanical load	5400 Pa / 550 kg/m ²


PACKAGING INFORMATION

Packing configuration	56 pcs / double pallet
Loading Capacity	672 pcs / 40HQ
Size / pallet (mm)	1985 x 1120 x 2410
Weight	1295 kg / pallet

CERTIFICATES



DIMENSIONS



AES-DSH2019 V.002
All rights reserved. Specifications included in this data sheet are subject to change without notice.

AE Solar GmbH

Messerschmittring 54
86343 Königsbrunn
Germany

Tel.: +49 8231 92 92 52 2
Fax: +49 8231 97 82 68 9
Email: sales@ae-solar.com
Web: www.ae-solar.com